



TEST REPORT

IEC 62471:2006

Photobiological safety of lamps and lamp systems

Colin zhang

Alice . lin



IEC 62471



IEC 62471

	$L_B t = \frac{700}{300} L(\lambda, t) B(\lambda) t^{-2} t^{-1}$	
	$L_B = \frac{700}{300} L(\lambda) B(\lambda)$	
	$E_B t = \frac{700}{300} E_\lambda(\lambda, t) B(\lambda) t^{-2}$	
	$E_B = \frac{700}{300} E_\lambda(\lambda) B(\lambda)$	
	$L_R = \sum_{\lambda=380}^{1400} L_\lambda \cdot R(\lambda) \cdot \Delta\lambda \leq \frac{50000}{0.25} W \cdot m^{-2} \cdot sr^{-1}$	

IEC 62471

	$E_{IR} = \sum_{780}^{3000} E_\lambda \cdot \Delta\lambda \leq 18000 \cdot t^{-0,75}$ W·m ⁻²	
	$E_{IR} = \sum_{780}^{3000} E_\lambda \cdot \Delta\lambda \leq 100$ W·m ⁻²	
	$E_H \cdot t = \sum_{380}^{3000} \sum_t E_\lambda(\lambda, t) \cdot \Delta t \cdot \Delta\lambda \leq 20000 \cdot t^{0,25}$ J·m ⁻²	



IEC 62471



IEC 62471



	IEC 62471		

FINAL



Table 4.1



Table 4.2



FINAL


Table 5.4						
Hazard Name	Relevant equation	Wavelength Range nm	Exposure aperture rad(deg)	Limiting aperture rad(deg)	EL in items of constant irradiance W.m ⁻²	

Table 5.5						-
Hazard Name	Relevant equation	Wavelength Range nm	Exposure duration Sec	Field of view radians	EL in terms of constant radiance W.m ⁻² .sr ⁻¹)	




Appendix I Figure of Spectral distribution

Spectral distribution of LED



Appendix A - EUT Photos

1. General view of LED





Appendix B Test equipment list